

DNG-2300

3-CHANNEL WHITE NOISE GENERATOR

3-CHANNEL WHITE NOISE GENERATOR

WE RECOMMEND USING TD2300 & SP2300. COMPATIBLE WITH ANY TYPE OF VIBRATION TRANSDUCERS & AUDIO SPEAKERS.

FEATURES:

- Laser & Microwave Surveillance Systems using Reflections from Windows
- Electronic Stethoscopes [Contact Microphones]
- Microphones built-in the Walls or Other Construction
- Other Vibro-Acoustic Methods of Information Leakage

DESCRIPTION:

The DNG-2300 white noise generator was created to keep conversations and information private. Conduct confidential meetings and speak freely in your office, conference room or any private space.

Listening devices, bugs, thin walls or the carrying of a voice don't stand a chance against the DNG-2300. When the white noise generator is paired with the transducers and speakers, it produces a low level audible interference by creating vibrations onto the surface of the walls in the protected space. If any form of eavesdropping devices are used it will block the voices and instead it will pick up and relay back the vibrational white noise created by the counter surveillance device. You'll want to have a good spread of transducers and speakers amongst the wall space, the number will depend on the size and construction of the room.

DNG-2300 SPECIFICATIONS

3-CHANNEL WHITE-NOISE GENERATOR

DIMENSIONS: 2.36 in. x 6.89 in. x 10 in.

WEIGHT: 4.85 lbs.

POWER: 220V | 50Hz

TRANSDUCER CHANNELS

MAX OUTPUT: 2 x 10W

FREQUENCY RESPONSE: 250-5000Hz

MIN. IMPEDANCE OF LOAD: 30ohm

ACOUSTIC CHANNEL

MAX OUTPUT: 1 x 8W

FREQUENCY RESPONSE: 250-6500Hz

MIN. IMPEDANCE OF LOAD: 80ohm



WWW.KJBSECURITY.COM | 800.590.4272 | SALES@KJBSECURITY.COM |   

DNG-2300

WHITE NOISE GENERATOR ACCESSORIES



TD-2300 TRANSDUCER | SET X4 OR X8

FEATURES:

- Attractive design, looks good in any interior
- Compact design, fits great on windows, walls and other structures
- Includes Mounting set to install on any surface

TD-2300 SPECIFICATIONS

TD2300 TRANSDUCER

IMPEDANCE: 4 Ohm
FREQUENCY RESPONSE: 58 Hz-12 kHz
DIMENSIONS: 2.13 in. x .83in.
WEIGHT: .56 lbs.
POWER: 10W

TRANSDUCER INCLUDES

TRANSDUCER
SPACER
MOUNTING DISK
WALL ANCHOR
BOLTS, SCREWS & PLASTIC DOWEL



SP-2300 ACOUSTIC SPEAKER | SET X1

FEATURES:

- Creates audible noise to fill the void/cavities from listening devices
- 3-way Directional Sound, can be disassembled into 3 speakers if the space isn't large enough to accommodate it behind the drop ceiling or in ventilation
- Connect up to 12 Speakers

SP-2300 SPECIFICATIONS

TD2300 TRANSDUCER

IMPEDANCE: 24 Ohm
DIMENSIONS: 4.33 in. x 3.15 in.
WEIGHT: .79 lbs.
POWER: 9W

SPEAKER INCLUDES

ACOUSTIC SPEAKER
TRIANGLE SPEAKER HOLDERS
3.28FT POWER CORD
USER MANUAL



WWW.KJBSECURITY.COM | 800.590.4272 | SALES@KJBSECURITY.COM | [f](#) [t](#) [in](#)